Meropunp

The choice for unprecedented safety

Medallu

- Simple rate setting
- Clear identification of alarms
- Clinician configurable rate range
- Double micro processor safety control





www.micrelmed.com



Micropump

The hard is a mm/24hr adjustable rate ambulatory syringe pump for the accurate infusion of drugs for hospital and home care needs.

- · Configurable rate range to avoid medication errors
- LCD display with clear information on flow rate and identification of alarms.
- Designed with dual micro-controller architecture for maximum safety
- · Safe and convenient syringe attachment

0					99 Wide range	
0	20			80	99	arning zone
0	20	30	60	80	99	
0	48			99	Limited range 99 Single rate	

APPLICATIONS

The MP so syringe driver is suitable for many applications where adjustable infusion of medication is required in hospitals, nursing homes and the community.

Convenient for intravenous, intra-arterial, intratechal, subcutaneous and intramuscular infusions

Indicative drugs infused are: analgesics, sedatives, chemotherapy agents, insulin, heparin, diuretics, bronchodilators...

Portable: provides continuity of medical treatment without discomfort, even during daily activities for home care patients.

ACCESSORIES

Each Comes complete with protective cover for mechanical and light protection, shoulder holster for ambulatory use, carrying pouch, instructions for use and a set of batteries.



(€ 0120

Company ISO 9001/EN 46001 SGS Yarsley certified

SPECIFICATIONS

Dimensions: 165X54X23 mm

Weight: 190g with 6 Alkaline LR03 AAA batteries
Battery life: 2-3 months, or more than 70 full infusions

at intermediate flow rate

Flow rate: 1 to 99mm/24hr (1 mm increments)

Adjustable rate range:

- Minimum and maximun rate can be configured to limit programming errors.
- Rate can be locked to one single value.
- · Rate titration during infusion (configurable option).

Prime facility (configurable option).

Audio and visual alarms:

- ·Warning zones for rate unusually high or low.
- End of travel with silent end of infusion (configurable option).
- Occlusion
- ·System failure (with auto-diagnostics)
- Automatic self test
- Low battery
- Depleted battery

IPX4 splash proof

Displacement speed accuracy: ±2%

Syringes: 10ml, 20ml, 30ml (5 and 50ml in option)

Safe and reliable: full featured with the most up-to-date safety circuits.

A dual micro-controller design continuously running self tests.

Complies with: EN 60601-1.



4 Ithakis Str., Pallini GR 153 51 Athens Greece Tel.: +30 2106032333 & 4, FAX: +30 2106032335